

ENVIRONMENTAL METER

TECHNICAL DATA

FEATURES

- 4-in-1 multi-function meter... anemometer, humidity meter, light meter and type-K digital thermometer
- Type K (NiCr-NiAl) thermocouple input jack
- High precision thin-film capacitance humidity sensor
- Photo diode and colour correction filter light sensor
- Velocity Units: m/s, kph, mph, knots, and fpm
- °F or °C and Lux or Ft-cd selectable
- Data Hold, Record (Max/Min)
- Includes battery

SPECIFICATIONS

Air Velocity Range: 0.2 to 30.0 m/s; 1.4 to 108.0 kph; 0.9 to 67.0 mph; 80 to 5910 fpm; 0.8 to 58.3 knots

Resolution: 0.1 m/s; 0.1 kph; 0.1 mph; 1 fpm; 0.1 knot

Temperature Range: -148 to 2372°F (-100 to 1300°C)

Resolution: 0.1°F (0.1°C)

Humidity Range: 0 to 95% RH

Resolution: 0.1%RH

Light Range: 0 to 20,000 Lux (0 to 2000 Ft-cd)

Resolution: 1/10 lux (0.1/1 ft-cd)

Power Supply: Single 9V battery

Dimensions: 6.1 x 2.4 x 1.3" (156 x 60 x 33mm)

Weight: 8.8 oz (160g)



ORDERING INFORMATION

LM-8000	Environmental Meter
LS-103	Air/Gas Probe
LS-104	Right Angle Surface Probe
LS-107	General Purpose Probe
LS-109	Surface Probe
LS-134A	Needle Tip Probe
LS-139	Surface Probe
CA-52A	Soft Carrying Case
CERTIMTF4	NIST Calibration Certificate
LM-8000-NIST	Environmental Meter & NIST

8792992297 / 8884441019

info@isagetechologies.com

www.isagetechologies.com