Large LED Temp / RH Logger

Features

- Wall Mountable Super Large LED Display easy to Read
- PC Program IS Available for Setting up Parameters of: Logger Sample Interval, Start / Stop, Date & Time, HI / LO Alarm Threshold, Unit Selection, Memory Points.
- Recording Function and Monitoring Function Powered by DC: (While in Logging Mode, use only DC Adaptor)
- Air Temperature or Dew Point (DP) Display and °C/°F Unit display are selectable
- Features Self-calibration for Humidity by Salt Bottle.
- Both Visible LEDs & Audible Warning Beeper
- LEDs' Indication:

 "REC" LED light flash means under recording mode,

 "ALM" LED light activate means reading exceeds threshold setting
- Tripod Mountable Device for Long Time Holding
- Rigid and palm size design with USB Interface



Model: 8809



SPECIFICATION

Display	Super Large LCD Size: 50.9 x 65.5mm
Range	Temp. : -20°C to 70°C RH : 0 to 100%
Accuracy Temp.	Temp. : ± 0.6°C (0 to 50°C), others ± 1.2°C
Accuracy Humidity	RH : ± 3% (10 to 90% @ 25°C) others ± 5%
Resolution	Temp. : 0.1°C / °F, RH : 0.1% Point (DP)

Display Style	Upper : RH%, Bottom : Temp. or DP
Memory Points	16000
Power Supply	Battery 4 pcs x AA or DC adaptor
Dimensions	120L x 93W x 42T mm
LED Signal	REC (Alarm) / °F or Dew
Optional Accessories	9 VDC Adaptor Salt Bottle (33% & 75%RH)